

SR-10-AN ACOUSTIC SYSTEM



KELONIK CINEMA SOUND

Surround channel cinema sound system

The system is specifically designed for high quality two-way surround-channel sound.

SR-10-AN system's cabinet has a high frequency constant dispersion driver-horn with 1" Ø dome, and a 10" Ø woofer.

Crossover is passive-type, with 2,000 Hz cut frequency.



APPROVED
THX


SR-10-AN has a switch to obtain two different response curves for the installations offering the following possibilities:

- 1) (ISO 2969) Response to ISO 2969 cinema surround roll-off curve.
- 2) (Flat) Flat response for improved high frequencies.

Approved for THX.

SR-10-AN ACOUSTIC SYSTEM

Mount SP SR-10-A



TECHNICAL DATA

Frequency Range (-10 dB)	50 Hz- 18 kHz
Nominal Impedance	8 Ω

POWER CAPACITY

Continuous Pink Noise ⁽¹⁾	200 W
Continuous Program	400 W
Sensitivity 1W/1m	96 dB S.P.L.
Crossover Frequency	2000 Hz
Horizontal Beamwidth	100°
Vertical Beamwidth	60°
Dimensions (H x W x D)	56 x 48 x 29 cm
Net Weight	16 kg

(1) Based on a 2 hour test using a continuous 6 dB crest factor pink noise signal band limited according to IEC 268-1 (1985).

COMPONENTS

Cabinet	SR-10-A
Low Frequency Driver	10-MI-K
Passive Crossover	F-SR-10-AN
High Frequency Horn	M-34K