



SPEAKER SETTINGS

		Fill in blank areas					
Contact person and phone #		Jordi Casas	#	+34 93 300 43 61			
e-mail		sk@kelonik.com					
1	MAKE	KCS					
2	Model	S-2001-D					
2a	Type (screen, surround, or sub)	SCREEN					
2b	full range, 2-way, 3-way, or dual low	2-WAY					
LOW FREQUENCIES							
3a	Nominal Impedance	4 ohms					
3b	HPF	Butt 24 dB/oct 35 Hz					
3c	LPF	LR 24 dB/oct 500 Hz					
3d	Gain (dB)	0 dB					
3e	Polarity						
3f	Delay (mS)						
3g	Output EQ	EQ1	EQ2	EQ3	EQ4	EQ5	EQ6
	Freq (Hz)	50 Hz					
	Q	3					
	Gain (dB)	+ 4,0 dB					
	Type	Parametric					
MEDIUM HIGH FREQUENCIES							
4a	Nominal Impedance	8 ohms					
4b	HPF	LR 24 dB/oct 500 Hz					
4c	LPF						
4d	Gain (dB)	- 6 dB					
4e	Polarity						
4f	Delay (mS)						
4g	Output EQ	EQ1	EQ2	EQ3	EQ4	EQ5	EQ6
	Freq (Hz)	10 kHz					
	Q	3					
	Gain (dB)	+ 6,0 dB					
	Type	Parametric					